



Product Service

# Attestation of Conformity

No. N8A 17 11 94747 011

**Holder of Certificate:** **Xinsu Global Electronic Co., Limited**  
Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road  
Central  
HONG KONG

**Product:** **Switching power supply unit  
(SWITCHING POWER SUPPLY/CHARGER)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

**Test report no.:** 652101711301

**Date,** 2017-12-07

( Ricky Wang )



**CE** After preparation of the necessary technical documentation as well as the EU conformity declaration the required CE marking can be affixed on the product. That declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

Page 1 of 3



**Attestation of Conformity**  
**No. N8A 17 11 94747 011**

**Model(s):**

XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM,  
 XSGxxxxxy, XSGxxxxxyzz, XSExxxxxy, XSExxxxyzz,  
 XSECxxxxxy, XSECxxxxyzz  
 (xxx=042-730, which denotes the rated output voltage  
 from 4.2VDC to 73.0VDC; yyyy=0300-9999, which denotes  
 the rated output current from 300mA to 9999mA; zz=EU or  
 UK, which denotes for marketing purpose and not affect  
 safety, EU=Europe, UK=United Kingdom.)  
 XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM,  
 XSGxxxxxy, XSGxxxxyzz, XSExxxxxy,  
 XSExxxxyzz, XSECxxxxxy, XSECxxxxyzz  
 (xxx=042-190, which denotes the rated output voltage from  
 4.2VDC to 19.0VDC; yyyy=10000-11000, which denotes  
 the rated output current from 10000mA to 11000mA;  
 zz=EU or UK, which denotes for marketing purpose and  
 not affect safety, EU=Europe, UK=United Kingdom.)

**Parameters:**

Rated Input :	100-240VAC, 50/60Hz, 3.0A Max.
Rated Output :	See page 3 for details
Protection Class :	I (For models XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM, XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM); II (For models XSGxxxxxy, XSGxxxxyzz, XSExxxxxy, XSExxxxyzz, XSECxxxxxy, XSECxxxxyzz, XSGxxxxxy, XSGxxxxyzz, XSExxxxxy, XSExxxxyzz, XSECxxxxxy, XSECxxxxyzz)
Degree of Protection :	IP20

**Tested  
 according to:**

EN 62368-1:2014

Attestation of Conformity  
 No. N8A 17 11 94747 011



Product Service

Model No.	Rated output voltage (VDC)	Rated output current (mA)	Max. rated output power (W)
XSGxxxxxyMM, XSExxxxxyMM,	4.2-9.0	10000	90.0
XSECxxxxxyMM,	9.1-14.6	10000-11000	160.6
XSGxxxxxy, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz	14.7-17.0	10000	170.0
XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz	17.1-19.0	10000	190.0
XSGxxxxxyMM, XSExxxxxyMM,	4.2-9.0	300-9999	90.0
XSECxxxxxyMM,	9.1-14.6	300-9999	146.0
XSGxxxxxy, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz	14.7-17.0	300-9999	170.0
XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz	17.1-19.0	300-9999	190.0
XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz	19.1-22.0	300-9500	190.0
XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz	22.1-32.0	300-8500	205.8
XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz	32.1-36.5	300-6000	219.0
XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz	36.6-57.9	300-5000	210.0
XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz	58.0-58.8	300-3600	210.2
XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz	58.9-73.0	300-3400	204.0