



Product Service

CERTIFICATE

No. Z1A 16 11 94747 004

Holder of Certificate: Xinsu Global Electronic Co., Limited
 Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road
 Central
 HONG KONG

Factory(ies): 94748

Certification Mark:



Product: Switching power supply unit
 (SWITCHING POWER SUPPLY)

Model(s): XSGxxxxxyyyzz, XSGxxxxyyyy, XSExxxxxyyyzz,
 XSExxxxyyyy, XSECxxxxxyyyEU, XSECxxxxyyyy
 (xxx = 036-588 which represent the rated output voltage
 from 3.6VDC to 58.8VDC; yyyy = 0100-7000 which represent
 the rated output current from 0.1A to 7.0A; zz = EU or UK,
 stands for sales markets,EU= Europe, UK= United Kingdom.)

Parameters:

Rated Input :	100-240VAC, 50/60Hz, 1.3A
Rated Output :	See page 2 for details
Protection Class :	II
Degree of Protection :	IP20

Tested according to: EN 61558-1:2005/A1:2009
 EN 61558-2-16:2009/A1:2013
 EN 60335-1:2012/A11:2014
 EN 62233:2008
 AfPS GS 2014:01 PAK 3.1

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.

Test report no.: 652501602401

Valid until: 2021-11-06

Date, 2016-11-10

(Michael Xu)

Page 1 of 2



CERTIFICATE
No. Z1A 16 11 94747 004



Product Service

Model	Rated output voltage (VDC)	Rated output current (mA)	Maximum rated output power (W)
XSGxxxxxyzz, XSGxxxxxy	3.6-5.0	100-7000	35.0
	6.0-9.0	100-6500	58.5
	10.0	100-6000	60.0
	11.0	100-5500	60.5
	12.0-12.6	100-5000	63.0
	13.0-14.0	100-4500	63.0
	14.6-15.0	100-4000	60.0
	16.0-30.0	100-4060	65.0
	32.0-58.8	100-2000	65.0
XSExxxxxyzz, XSExxxxxy, XSECxxxxxyEU, XSECxxxxxy	3.6-5.0	100-7000	35.0
	5.1-9.0	100-6500	58.5
	10.0-12.0	100-6000	60.0
	11.1-12.6	100-5000	63.0
	12.8-15.0	100-4500	65.0
	16.0-20.0	100-3750	65.0
	21.0-30.0	100-3000	65.0
	31.0-58.8	100-2000	65.0